



On the Interpretation of Error Contours

Prepared by
R. H. GERSTEN
Satellite Navigation DepartmentGuidance and Control Division

Guidance and Control Division The Aerospace Corporation El Segundo, Calif. 90245

SELEC:
DEC 1.6/1980
E

30 September 1986

Final Report

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

Prepared for

SPACE DIVISION
AIR FORCE SYSTEMS COMMAND
Los Angeles Air Force Station
P.O. Box 92960, Worldway Postal Center
Los Angeles, Calif. 90009

410 01/1

DDC FILE COF

80 12 10 013

This final report was submitted by The Aerospace Corporation, El Segundo, CA 90245, under Contract F04701-79-C-0080 with the Space Division, Deputy for Space Communications Systems, P. O. Box 92960, Worldway Postal Center, Los Angeles, CA 90009. It was reviewed and approved for The Aerospace Corporation by D. J. Griep, Engineering Group. First Lieutenant J. C. Garcia, YLXT was the Deputy for Technology project engineer.

This report has been reviewed by the Public Affairs Office (PAS) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nations.

This technical report has been reviewed and is approved for publication. Publication of this report does not constitute Air Force approval of the report's findings or conclusions. It is published only for the exchange and stimulation of ideas.

J. C. Garcia, lst Lt, USAF

Project Engineer

Joseph J. Cox, JC, LtCol, USAF Chief, Advanced Technology Division

FOR THE COMMANDER

Burton H. Holaday, Col, USAF

Director, Directorate of Space Systems Planning

Deputy for Technology

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

	(9) REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
18	SD-TR-80-83 2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
6	4. TITLE (and Subtitle)	S. TYPE OF REPORT & PERIOD COVERED
<u>`</u> -{	ON THE INTERPRETATION OF ERROR CONTOURS	TR-0080(5991-03)-2
	7. AUTHOR(s)	S- CONTRACT OR GRANT NUMBER(a)
11	R. H./Gersten	F04701-79-C-0080
	The Aerospace Corporation El Segundo, CA 90245	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
	Space Division, Air Force Systems Command	30 September 1380
	P.O. Box 92960, Worldway Postal Center Los Angeles, Calif. 90009	NUMBER OF PAGES
Ì	14. MONITORING AGENCY NAME & FDDRESS(II dillerent from Controlling Office)	15. SECURITY CLASS: (ST mis Topon)
		Unclassified
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
	Approved for public release; distribution unlimited. 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, 15 different from	
	18. SUPPLEMENTARY NOTES	
	19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Error Contours Error Ellipses	
	Circular Error Probability (CEP)	
	Error Ellipsoids Spherical Error Probability (SEP) Normal Probability Distribution	
1	20. ABSTRACT (Continue on reverse elde if necessary and identify by block number)	
	Although frequently encountered in engineering probl contours has been the subject of much debate and conthis report attempts to clarify this situation by deprincipals without rigorous derivation.	nfusion among engineers.
	While the material presented here may be well known theorists, it appears that this exposition is require	among a miniscule clique of ed by the engineering

DD FACS W. 413

. प्राप्त के किया के जिल्ला के किया के अपने के अपने के अपने के अपने के किया के किया के किया के किया के किया के

CONTENTS

I.	INTRODUCTION	5
II.	THE NORMAL CURVE	7
III.	ERROR ELLIPSES AND ELLIPSOIDS	11
IV.	SPHERICAL ERROR CONTOURS	17
٧.	COMPARISON OF TWO-DIMENSIONAL ERROR CONTOURS	19
VI.	SUMMARY	23
APPEN	DIX - COMPUTATION OF 50 AND 95 PERCENT PROBABILITY CIRCLES FROM THE PRINCIPAL AXES OF THE 10 ERROR ELLIPSE	25
REFER	ENCES	27

Access	ion For	
NTIS		X
DDC TA		
Unennounced		
Justif	ication_	
Ву		
Distribution/		
Availed ty Codes		
	Availan	d/or
Dist.	specia	1
	1	
14	1	
111		

FIGURES

1.	Normal Distribution	8
2.	Three Normal Curves With the Same Mean and Different Standard Deviations	9
3.	l and 2σ Error Ellipses	12
4.	lo Error Ellipsoid	13
5.	p_n (k) vs. k for n = 1,2,3	16
6.	Two-Dimensional Gaussian Probability Distribution	20
7.	Gaussian Error Ellipses	21
8.	Common Error Contours for Two-Dimensional Gaussian Distribution	22
	TABLES	
1.	Table of p(k) vs. k for One-Dimensional Normal Distribution	10
2.	Table of k for Selected p _n (k)	14
3.	Table of p _n (k) for Selected k	15

 $\star_{\mathcal{A}} \cdot \star_{\mathcal{A}} = \star_{\mathcal{A}} \cdot \star_{\mathcal{A}}$

I. INTRODUCTION

Although contours such as circular error probabilities (CEPs), error ellipses, etc., are frequently encountered in engineering problems, their meaning is often misunderstood. For example, it is not common knowledge in the engineering community that a lo (three-dimensional) ellipsoid carries a different probability confidence level than a lo (two-dimensional) ellipse, or for that matter a lo (one-dimensional) line segment. Also, there is confusion over the relationship between elliptical and spherical error contours.

This report attempts to clarify this situation. To help explain, results are presented heuristically, without rigorous derivation. The discussion begins with a brief review of the properties of the "normal" probability distribution.

II. THE NORMAL CURVE

The most commonly encountered probability distribution in statistics is the so-called "normal" or "Gaussian" distribution presented in Fig. 1. Here, the abscissa corresponds to the observations y. The total area under the curve is equal to unity and the area lying between specified abscissa points is a measure of the relative frequency of observations between these limits.

The normal curve is completely specified by two parameters, the mean μ and the standard deviation σ . Note that the curve is "bell-shaped" and symmetric with respect to a line drawn perpendicular to the abscissa at the mean.

The standard deviation σ defines the spread of the curve. Figure 2 exhibits three normal curves having equal means but different standard deviations. Curve A with the largest spread has the largest standard deviation and Curve C the smallest. The symmetric property of the normal distribution requires that 50 percent of the observations fall below the mean and 50 percent above it. In terms of probability, the probability for an observation falling either above or below the mean is 0.50. Approximately 34 percent of the observations lie in the interval μ to μ + σ . Thus, from the symmetric property, the probability of an observation falling between μ - σ and μ + σ is 0.68.

Since μ and σ uniquely define a normal distribution, unique probabilities can be assigned to all regions within this distribution. Thus, Table 1 presents probabilities p (k) associated with selected μ - k σ to μ + k σ limits. This table indicates, for example, that 95 percent of the observations lie in the region specified by k = 1.960 from μ - 1.960 σ to μ + 1.960 σ .

Thus far the discussion has been limited to probabilities associated with a normally distributed scalar variable. In the next section, the scope of the discussion is extended to encompass variables of two and three dimensions.




Fig. 1. Normal Distribution





Fig. 2. Three Normal Curves with the Same Mean and Different Standard Deviations

Table 1. Table of p(k) vs. k for One-Dimensional Normal Distribution

p(k)	k
0.05	0.0627
0.10	0.126
0.15	0.189
0.20	0.253
0.25	0.319
0.30	0.385
0.35	0.454
0.40	0.524
0.45	0.598
0.50	0.674
0.55	0.755
0.60	0.842
0.65	0.935
0.70	1.036
0.75	1.156
0.80	1.282
0.85	1.440
0.90	1.645
0.95	1.960



III. ERROR ELLIPSES AND ELLIPSOIDS

Let x and y denote perpendicular axes lying in a plane. Assume that independent normally distributed observations along these axes have means μ_x and μ_y and standard deviations σ_x and σ_y , respectively (Fig. 3). The lo error ellipse, pictured in Fig. 3 is defined as that ellipse centered at (μ_x, μ_y) with principal semiaxes of σ_x and σ_y . Similarly, for any real number k, the ko error ellipse (k = 1,2,3, ...) is centered at (μ_x, μ_y) with principal semiaxes of ko and ko.

In an analogous manner, let x, y, and z define three orthogonal coordinates in space. Again, assume independent normally distributed observations along these axes with means denoted by μ_x , μ_y , μ_z and standard deviations by σ_x , σ_y , σ_z (Fig. 4). Then, the ko error ellipsoid is defined as that ellipsoid centered at (μ_x, μ_y, μ_z) with principal semiaxes $k\sigma_x$, $k\sigma_y$, $k\sigma_z$. One octant of a lo error ellipsoid is given in Fig. 4.

Let $p_n(k)$ denote the probability that a given observation falls within a ko error contour of n-dimensions; n of 1, 2, and 3 corresponding to line segments, ellipses and ellipsoids, respectively. This probability is obtained directly from the so-called "chi-square" probability distribution with n degrees-of-freedom; n = 1 yielding the normal distribution discussed in the previous section.

Tables 2 and 3, taken from Ref. 1, extend the one-dimensional results of Table 1 to two and three-dimensions. These tables reveal that probability confidence levels decrease with increasing dimension. Thus, for example, the 1σ levels are:

 p_1 (1) = 68% - line segment (one-dimension)

 p_2 (1) = 39% - ellipse (two-dimensions)

 p_3 (1) = 20% - ellipsoid (three-dimensions)

Here, specifically, p_1 (1) is the probability that a <u>single</u> random variable lies within its lo limits. However, p_2 (1) and p_3 (1) are probabilities that <u>all</u> random components lie within the bounding ellipse or ellipsoid. In short, for n > 1, p_n (1) assumes simultaneity, while p_1 (1) does not. Indeed, p_n (k) is always smaller than p_1 (k) (Fig. 5).




Fig. 3. 1 and 20 Error Ellipses




Fig. 4. lo Error Ellipsoid

Table 2. Table of k for Selected p_n (k)

	1	n 	
p _n (k)	1	2	3
0.05	0.0627	0.320	0.59
0.10	0.126	0.459	0.75
0.15	0.189	0.570	0.89
0.20	0.253	0.668	1.00
0.25	0.319	0.759	1.10
0.30	1.385	0.844	1.19
0.35	0.454	0.928	1.28
0.40	0.524	1.011	1.36
0.45	0.598	1.093	1.45
0.50	0.674	1.177	1.53
0.55	0.755	1.264	1.62
0.60	0.842	1.354	1.71
0.65	0.935	1.449	1.81
0.70	1.036	1.552	1.91
0.75	1.156	1.665	2.02
0.80	1.282	1.794	2.15
0.85	1.440	1.948	2.30
0.90	1.645	2.146	2.50
0.95	1.960	2.448	2.79
0.98	2.326	2.797	3.13
0.99	2.576	3.035	3.30
0.995	2.807	3.255	3.5

Table 3. Table of p_n (k) for Selected k

η			
k	1	2	3
0.2	0.158	0.0198	0.00210
0.4	0.311	0.0769	0.0162
0.6	0.451	0.164	0.0516
0.8	0.576	0.274	0.113
1.0	0.683	0.393	0.199
2.0	0.954	0.865	0.739
3.0	0.997	0.989	0.971
4.0	1.000	1.000	0.999
5.0	1.000	1.000	1.000




Fig. 5. p_n (k) vs. k for n = 1, 2, 3

IV. SPHERICAL ERROR CONTOURS

One disadvantage of displaying results in terms of error ellipses or ellipsoids is that several numbers are required. For example, the specification of an error ellipse requires three numbers, the magnitude of the two principal axes and an orientation angle. Similarly, six numbers are required to specify an ellipsoid, the magnitudes of the three principal axes and three orientation angles.

A possible alternative is to present results in terms of circles or spheres having a particular probability level. Although this approach may seem appealing at first, it has some disadvantages. Unless the principal axes of the ellipse or ellipsoid are nearly equal, use of the corresponding circle or sphere can lead to serious errors in engineering judgment, since all information regarding preferred directions is lost. In addition, the desired radius is not easily determined. Special algorithms for this computation are given (Refs. 2, 4). The cases where p_2 (k) = 0.50 and p_3 (k) = 0.50 correspond, respectively, to the well-known circular error probability (CEP) and spherical error probability (SEP). From Table 2, these last carry probability levels equal to those of the 1.177- σ ellipse and the 1.538- σ ellipsoid.

A procedure for computing both the 50 and 95 percent probability circles from the principal semiaxes of the lo ellipse is presented in Appendix A. This technique uses linear interpolation between values of the principal semi-axes and radius as listed in the extensive tables of Ref. 3.

V. COMPARISON OF TWO-DIMENSIONAL ERROR CONTOURS

The analog in two-dimensions to the one-dimensional Gaussian distribution in Fig. 1 is presented in Fig. 6. Maintaining previous notation, x and y lie along the principal axes of the error ellipse, and f is the frequency of the observations, while x' and y' are the observation axes in the x-y plane. It is observed in this figure, and indeed in general, that principal and observation axes are not collinear. In statistical terms, this means the observations are correlated. The probability surface is depicted as a "mountain" symmetric about the two planes containing the f-axis and one principal axis.

The total volume under the surface is equal to unity. Thus, the volume intercepted by circular or elliptical cylinders with axes parallel to f is a measure of the frequency of observations within the enclosed area on the x'-y' plane. Of course, circular cylinders yield circular intercepts such as the CEP and 95 percent probability circle, while error ellipses result from elliptical cylinders.

Figure 7 exhibits a family of ellipses for the two-dimensional normal distribution of Fig. 6. These ellipses, all of which have major to minor axis ratios of five to one, are obtained by slicing the probability "mountain" parallel to the x-y plane at various heights along the f-axis.

Five of the more commonly encountered contours associated with this probability distribution; the 1, 2 and 3 σ ellipses, CEP, and 95 percent circle, are illustrated in Fig. 8. Superimposed upon this figure are computer-generated points randomly selected from a population with the same probability distribution.

One immediately notes that the elliptical representations contain much more information about the distribution of the points. Thus, for this example, the 3 σ ellipse encloses more points than does the 95 percent circle while requiring only about half the area. As a general rule, elliptical contours are preferable except when the magnitudes of the principal axes are nearly equal.




Fig. 6. Two-Dimensional Gaussian Probability Distribution





Fig. 7. Gaussian Error Ellipses



Common Error Contours for Two-Dimensional Gaussian Distribution Fig. 8.

VI. SUMMARY

In ascertaining the relative merits of elliptical vs. spherical error contours in reporting system errors, the more weighty arguments can be advanced in favor of the former. Not only do the error ellipse and ellipsoid convey more information than the CEP and SEP, they are actually easier to compute. The sole argument favoring the latter pair is that their specification requires only a single number.

However, the utilization of lo ellipses (or ellipsoids) can be very misleading to the uninitiated. Thus, the temptation to assume that the lo ellipse encloses at least a majority of cases, as does the one-dimensional lo line segment, is overwhelming. The truth is that the lo ellipse subtends only 39 percent of the cases. The situation is even more exaggerated in three-dimensions, where the lo ellipsoid encloses only 20 percent of the cases. The alternative is clear. Instead of using lo ellipses (or ellipsoids) one should use 50 or 95 percent ellipses (or ellipsoids). Here the name itself indicates the percentage of cases subtended and no confusion results.

APPENDIX

COMPUTATION OF 50 AND 95 PERCENT PROBABILITY CIRCLES FROM THE PRINCIPAL AXES OF THE 10 ERROR ELLIPSE

This appendix contains a technique for computing the radii of the 50 and 95 percent probability circles, R50 and R95, from the major and minor semiaxes of the 10 error ellipse, denoted λ maj and λ min respectively. In particular, the desired radius R is obtained by linear interpolation between values of λ maj, λ min and probability as listed in the tables of Ref. 3. The use of linear interpolation is justified by the observation that the normalized quantities λ min / λ maj and R/ λ maj are nearly linearly related over wide regions.

Begin by defining the four 10-dimensional vectors

- Y50 = (0.6820, 0.7059, 0.7499, 0.8079, 0.8704, 0.9336, 0.9962, 1.0577, 1.1181, 1.1774)
- SL50 = (0.0075, 0.02386, 0.04408, 0.05792, 0.06256, 0.06323, 0.06256, 0.06149, 0.06036, 0.05935)
- Y95 = (1.962, 1.970, 1.984, 2.005, 2.036, 2.081, 2.146, 2.230, 2.332, 2.448)
- SL95 = (0.006, 0.008, 0.014, 0.021, 0.031, 0.045, 0.065, 0.084, 0.102, 0.116)

where the Y's and SL's represent values of R / λ maj and slope associated with intervals of 0.1 in λ min / λ maj for the 50 and 95 percent radii. The proper component of the Y and SL vectors, I, and the interpolation interval, DEL, are computed from

 $X = 10 \lambda \min / \lambda \max j$

I = Integer part of X + 1 or 10 whichever is smaller

DEL = X - I

Then the desired radii result directly from linear interpolation via

R50 = $[Y50(I) + SL50(I) DEL] \lambda maj$

R95 = $[Y95(I) + SL95(I) DELj \lambda maj$

REFERENCES

- 1. R. H. Gersten, and I. A. Gura, "On Analysis of n-Dimensional Normal Probabilities," TR-0066(5129-01)-2, The Aerospace Corporation (2 June 1970).
- 2. C. R. Greenwalt, and M. E. Shultz, "Principles of Error Theory and Cartographic Applications," Report No. 96, Aeronautical Chart and Information Center, St. Louis, Mo., February 1962.
- 3. C. Groenewoud, D. C. Hoaglin, and J. A. Vitalis, <u>Bivariate Normal Offset Circle Probability Tables</u>, Vol. I and II, Cornell Aeronautical Lab.

 Inc., CAL NO. XM-2464-G-1, Dec. 15, 1957.
- 4. R. J. Schulte, "Four Methods of Solving the Spherical Error Probable Associated with Three-Dimensional Normal Distribution," AD 666646, Holloman Air Force Base, New Mexico, January 1968.